

## 769900 Series 1310 nm Fiber Optic Transmitters


 Televés


The Televés 769900 optical transmitters represent the latest in design and technology in RF fiber optic transmitters. These transmitters feature a 1310 nm optical output for SMATV or 2 way cable TV system transmissions where RF over fiber works best.

It has a 54-2400 MHz bandwidth so it is compatible with satellite L-band and DOCSIS 3.1 systems. These fiber transmitters are equipped with automatic gain control (AGC), and use cooled DFB lasers for stability. They are built in a 1 RU 19" rackmount chassis with universal 100-253 VAC power supply.

### Features:

- 47-2400 MHz Bandwidth
- 6 dBm or 10 dBm Optical Output
- 1310 nm
- DFB Laser
- 0-14 dB Manual Gain Adjustment
- Key Control for Safety
- AGC
- SC/APC Optical Connector
- 12-32 dBmV Input Level Range
- 1RU Rackmount
- Model 769902 (6 dBm)
- Model 769903 (10 dBm)

### Ordering Information:

<b>769902</b>	1310 nm, 6 dBm Optical Transmitter
<b>769903</b>	1310 nm, 10 dBm Optical Transmitter

## 769900 Series 1310 nm Fiber Optic Transmitters

RF Parameters	Bandwidth	47... 2400 MHz
	Input Level Range RF	15...30 dBmV
	Input Level Satellite	RF – 10 dB
	Manual Gain Adjustment	0 ... 14 dB (2 dB steps)
	AGC Range	20 dB
	Flatness (47...1218MHz)	± 0.5 dB
	Flatness (950...2400MHz)	± 2 dB
	Return Loss (47...1218MHz)	≥ 10 dB
	Return Loss (950...2400MHz)	≥ 7 dB
	Impedance	75 Ohm
	CSO (CENELEC 42)	≥ 60 dB
	CTB (CENELEC 42)	≥ 60 dB
	C/N	>50 dB
Optical	Laser	DFB
	Wavelength	1310 nm
	Output Level 769902	5 dBm (3.2 mW)
	Output Level 769903	10 dBm (10 mW)
	Connector	SC/APC (Green)
	Power Supply Voltage	99 to 253 VAC
General	Power Supply Frequency	50 or 60 Hz
	Power Consumption	≤ 25 Watts
	Size W x H x D	19" x 1.75" x 8"
	Weight	7 lbs
	Temperature Range	32° - 110° F