



ACA Series

Apartment Complex Amplifiers



ACA-30-xxR



ACA-30-550

The ACA Series are indoor CATV RF distribution amplifiers designed to be used in RF distribution systems such as those for apartment complexes, hospitals, schools, prisons, and hotels. Two way models are available in 550, 750 and 860 MHz bandwidths with a passive return path of 5-30 MHz. A one way model is also available in a 550 MHz bandwidth only.

ACA's are housed in a compact, aluminum chassis that provides excellent heat dissipation. An external power transformer is provided for use with 117 VAC power. The unit can also be powered directly with 24 VAC.

- (a) Measured at full gain with 0 dB slope.
- (b) At rated output capability and channel loading.
- (c) The ACA-30 Series can be powered via 117 VAC using the included transformer or via 24 VAC without the transformer

Features & Benefits

- Models Available in 550, 750 and 860 MHz Bandwidths
- Built-in Variable Gain and Slope Controls
- Push-Pull Hybrid Module Design
- Aluminum Chassis Provides Excellent Heat Dissipation
- 5-30 MHz Passive Return Models

Specifications

RF

Frequency Range (MHz):
Channel Loading:
Flatness (dB):
Gain (Reverse) (dB):
Noise Figure (dB) (a):
Output Level (dBmV) (d):
Gain Control Range (dB):
Slope Control Range (dB):
Composite Triple Beat - CTB (dB) (b):
Cross Modulation - XMOD (dB) (b):
Composite Second Order - CTB (dB) (b):
Hum Modulation (dB):
Return Loss
Input (dB):
Output (dB):

General

Power Requirements
Voltage (VAC) (c):
Frequency (Hz):
Power (W):
Temperature Range (°C):

Mechanical

Dimensions (LxWxD):
(in)
(mm)
Weight:
(lbs)
(kg)

	ACA 30-550	ACA 30-55R	ACA 30-75R	ACA 30-86R
Frequency Range (MHz):	47-550	5-30 47-550	5-30 47-750	5-30 47-860
Channel Loading:	77	77	110	129
Flatness (dB):	±1.00	±1.00	±1.00	±1.00
Gain (Reverse) (dB):	32, (-)	31, (-.75)	31, (-.75)	31, (-.75)
Noise Figure (dB) (a):	7.0	8.5	9.0	9.0
Output Level (dBmV) (d):	+36/+44	+36/+44	+34/+44	+34/+44
Gain Control Range (dB):	20	15	15	15
Slope Control Range (dB):	10	10	10	10
Composite Triple Beat - CTB (dB) (b):	-64	-64	-63	-56
Cross Modulation - XMOD (dB) (b):	-64	-64	-62	-58
Composite Second Order - CTB (dB) (b):	-64	-58	-64	-58
Hum Modulation (dB):	-65	-65	-65	-65
Return Loss				
Input (dB):	14	12	12	12
Output (dB):	14	12	12	12
Power Requirements				
Voltage (VAC) (c):	117, ±10% 24	117, ±10% 24	117, ±10% 24	117, ±10% 24
Frequency (Hz):	60	60	60	60
Power (W):			19	19
Temperature Range (°C):	-20 to +60	-20 to +60	-20 to +60	-20 to +60
Dimensions (LxWxD):				
(in)	8.00 x 5.50 x 2.50	7.50 x 5.63 x 2.00	7.50 x 5.63 x 2.00	7.50 x 5.63 x 2.00
(mm)	203 x 146 x 64	191 x 143 x 51	191 x 143 x 51	191 x 143 x 51
Weight:				
(lbs)	4.1	3.1	3.1	3.1
(kg)	1.86	1.36	1.36	1.36

Ordering Information

Model	Stock No.	Description
ACA-30-550	5450	Apartment Complex Amplifier 30dB, 47-550MHz
ACA-30-55R	5750	Apartment Complex Amplifier 30dB, 47-550MHz, Passive Return, Single Hybrid
ACA-30-86R	5780	Apartment Complex Amplifier 30dB, 47-860MHz, Passive Return, Dual Hybrid
ACA-30-75R	5770	Apartment Complex Amplifier 30dB, 47-750MHz, Passive Return, Dual Hybrid