



QIP-D

IPTV Decoder / Controller



The Contemporary Research QIP-D IPTV Decoder/Controller is an integration friendly IPTV decoder with incorporated display control. The unit is part of a family of products from Contemporary Research that can be used to form an end-to-end IPTV distribution system with control.

The decoder is compatible with unicast or multicast UDP and RTP IPTV streams and will accept MPEG2 or H.264 single program or multiple program transport streams. A channel list of programs is uploaded from a PC running CR Toolbox software. Channel selection, volume, and power may be controlled from the front panel buttons, handheld IR remote, or external control system.

The QIP-D IPTV Decoder/Controller can receive commands from an ICE-HE-DXL Display Control Center or Display Express software for channel selection, volume control, power, and display source selection. Power and source selection will be translated to the protocol required for the connected display and transmitted out the RS-232 port.

FEATURES

Video

- HDMI selectable video output resolutions: 480i, 480p, 720p, 1080i, 1080p, and 4K or auto

Audio

- HDMI embedded AC3, PCM-fixed, or PCM-variable
- SPDIF optical AC3, PCM-fixed, or PCM-variable
- Analog stereo

Setup and Control

- Receives commands from Display Express software or the ICE-HE-DXL display controller over Ethernet for channel selection, volume, and display control
- Channel list loaded or updatable from CR Toolbox
- Channel selection by direct channel entry or channel up/down
- Control via front panel, optional IR remote, web GUI, Display Express software or serial commands from ICE-HE-DXL
- RS-232 for display control
- Setup via On-screen menu, web GUI, serial commands
- Firmware updateable over Ethernet from CR Toolbox

QIP-D

IPTV Decoder / Controller

SPECIFICATIONS

Physical Description

Size (HWD): 7.25" [184mm] wide (7.85" [200mm] including wings) x 1.150" [29mm] height x 3.6" [91mm] deep

Weight: 13 oz [369 g]

Enclosure: Aluminum with black powder coat paint


Mounting: Hook-and-loop fasteners or screw attachment

Power: PoE, 6W or 11 to 14 VDC at 0.5A max

Decoding

- Accepts UDP and RTP Ethernet streams
- Decodes MPEG2 or H.264 IPTV streams with AC3, MP1/2 or AAC audio
- Supports single program or multiple program transport streams
- Supports multiple audio programs
- On board closed caption decoder supports EIA-608 and EIA-708 embedded closed captions

Front Panel




IR: IR Sensor

Status: Red/green status LED

Control: Five button control

Back Panel



Service: USB-A port (internal use)

HDMI: Type A, 4K/HD video and digital audio

SPDIF: Optical digital audio output

Audio: 3.5mm stereo jack

RS-232: DB-9 male for display control

Ethernet: RJ-45 connector, 100Mbps, PoE

I/O: Optional USB Power Sensor Cable

IR In: 3.5 mm stereo jack for optional external IR receiver or wired IR

12VDC: Optional power input

2.1mm coaxial jack (inside center conductor positive), 0.5A max