

MicroLine

SD/HD Digital Settop Converter



Digital MPEG2/H.264 Settop with XCrypt Conditional Access

- SD / HD support (MPEG4 AVC/H.264)
- User friendly Installation • 7 fndh7 5 G
- USB PVR Function (with external HDD)
Time Shift Mode (with external HDD)
- Event Timer by EPG
- High Definition Video output : HDMI
- S/PDIF Dolby (coaxial)
- Subtitle support : OSD & VBI insertion for TV
- 4-segment LED Display
- Channel sorting by FTA, CAS, Alphabetic order & Network
- EPG : Now and Next and 7 days EPG
- Variable Input Symbol Rate
- User selectable output resolution
- Multi language OSD
- Fast Channel Change
- Memory for up to 5,000 TV & Radio Channels
- PIG (Picture In Graphic)
- 8 Favourite List & Unlimited Programs per each
- Channel Edit Function
 - Move, Delete, Favorite Edit
 - Parental Lock, Channel Rename, Channel Skip
- Manual PID & TP/ Network Scan
- S/PDIF – coaxial (Digital Audio or Dolby AC3 stream out)
- Software Upgrade via OTC & USB

Included Accessories - RCU, RCA cable, <8 A=VU'Y'Z
Power adapter, and Manual

Specifications Subject To Change Without Notice

Rev 10-16

© Toner Cable Equipment, Inc.

Memory and Chip

CPU	3812
DDR2	128MB
FLASH	8MB

A/V Rear Port

HDMI	1 (1.3)
AV-Jack	Video, Audio Output
Digital Audio (S/PDIF)	Coaxial
USB 2.0 rear	1

Front Panel

Display	4digits7segment display
Front Panel Keys	3key

Remote Control

Type	Infrared (Carrier Freq. 38kHz)
Battery	2 x 1.5 V AAA

Physical Specifications

Dimension (W x D x H)	5.7 x 1.1 x 3.9"
Operation Temperature	0 – 40° C

Power Supply

Input Voltage	External Power 12V / 1A
---------------	-------------------------