

AM

Style Lockable Wall Boxes Dual Module

FibreFab offers a wide range of indoor wall mounted splice enclosures the AMW enclosure offers a compact solution to the end user. This enclosure has been designed to accept up to 2 LGX style assemblies.

With the ability to use a full array of adaptor types offering a flexible solution to the end user, enabling them to incorporate a multi functional enclosure which allow easy access during installation or re-work with no disturbance of the existing cable or fibres.

In addition to the array of adaptors the enclosure also offers multiple cable entry solutions, fibre cable can be spliced or pre terminated solutions, making this enclosure one of the most flexible on the market.

Features

- ▶ Up to 2 LGX components
- ▶ Wall mountable
- ▶ Multiple adaptor options available
- ▶ Splicing option available.
- ▶ Lockable Hinged door.
- ▶ Accepts loose tube and distribution cable
- ▶ ROHS, REACH SvHC.

Applications

- ▶ Data centres, premise installations, telecommunication networks.
- ▶ Ethernet, Fibre Channel, ATM, LAN, MAN and WAN
- ▶ Data communication and telecommunication networks
- ▶ Indoor applications.

Technical Specification

| Specification | |
|-----------------------------|--|
| Height | 164mm |
| Width | 313mm |
| Depth | 120mm |
| Net weight | 3.2kg |
| Packaged weight | 3.5kg |
| Packaged dimensions | 230mm (W) x 350mm (L) x 160mm (H) |
| Suitable for Adaptor type | LGX / MTP Cassettes |
| Number of module positions | 2 |
| Material | Cold-rolled steel |
| Material thickness | 2.5mm |
| Material finish | Powder coating |
| Colour | RAL 9004 |
| Operating temperature | -40°C to +60°C |
| Designed in accordance with | TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754, EN297-1 |
| Compliant to | RoHS, Reach/SVHC |

