

# INLINE

## Fiber Splice Enclosure

The FibreFab inline enclosure is suitable for protecting fibre cable splices in straight through and branching applications. Its well-engineered injection moulded outer body make it impenetrable to the elements. It can protect splices and ensure reliability and usage in ambient temperatures from -40°C to +65 °C. It can be placed in aerial, underground, wall mounting, and duct mounting locations.

- ▶ 3 cable entry position at each end
- ▶ Termination and splice kit included
- ▶ Integrated seal, air tight and water proof
- ▶ Can be used in through, branch or mid span splice locations
- ▶ Suitable for aerial, underground duct or direct burial applications
- ▶ Ideal for cable repair
- ▶ RoHS compliant
- ▶ Integrated pressure valve
- ▶ Holds 24 to 192 splices
- ▶ Easy to re-enter
- ▶ IP68

### Technical Specification

<i>Dome Enclosure up to 144 fibres Capacity</i>	
Length	260mm
Width	170mm
Depth	70mm
Weight	0.6kg
Packaged Dimensions	290mm (L) x 190mm (W) x 80mm (H)
Packaged Weight	0.9kg
Maximum Single Fibre Count	24
Maximum Fibres Per Tray	12
Maximum Number Of Trays	2
Number Of Cable Entry Points	4
Cable entry diameter	8mm - 16mm
Sealing Rating	IP68
Colour	Black
Material	ABS
RoHS Compliant	Yes
Optimal Operating Temperature	-40°C to +80°C

### Ordering Information

<i>Description</i>	<i>Part No.</i>
24 Splice Inline enclosure	INLINE01
48 Splice Inline enclosure	INLINE02
72 Splice Inline enclosure	INLINE03
144 Splice Inline enclosure	INLINE04
196 Splice Inline enclosure	INLINE05

