

FPM Series Fiber Optic Power Meter



Designed to measure both the absolute optical power and relative power loss in fiber optic cables. These power meter features the following:

- Measures a wide variety of wavelengths from 800-1650 nm, with a mere 0.01 dB resolution
- Measures 6 preset calibrated wavelengths with high precision to determine absolute or relative power
- Special function of the unit allows the device to be manually calibrated as needed
- Comes with FC and SC adapters so that fiber connectors can be directly connected to the tool
- LED screen is backlit for viewing in low light locations and a 10 minute auto-off helps preserve battery life
- Dust-proof button design and shatter-resistant sleeve protect the tool to last a lifetime
- Recommended for use with FLS-50 optical light source. (See page 2).
- **FPM-50** includes: Fiber Optic Power Meter, Instruction Manual, Protective Cover, (3) AA Batteries (required for operation), (2) Cleaning Swabs, FC Adapter, SC Adapter & Nylon Carrying Case
- **FPM-50A** includes: FPM-50 and all the components listed above as well as the **VFL-25125** (LC Adapter.)

SPECIFICATIONS	FPM-50	FPM-50A
CONNECTOR TYPES	FC, SC	FC, SC, LC
CALIBRATED WAVELENGTHS (NM)	850, 980, 1300, 1310, 1490, 1550, 1625, 1650	850, 980, 1300, 1310, 1490, 1550, 1625, 1650
DETECTOR TYPE	InGaAs	InGaAs
MEASUREMENT RANGE	-50 dBm to +26 dBm	-50 dBm to +26 dBm
SINGLE MODE RANGE	980, 1310, 1490, 1550, 1625, 1650 nm, $\leq \pm 0.25$ dB	980, 1310, 1490, 1550, 1625, 1650 nm, $\leq \pm 0.25$ dB
MULTI MODE RANGE	850, 1300 nm, $\leq \pm 0.8$ dB	850, 1300 nm, $\leq \pm 0.8$ dB
RESOLUTION	0.01 dB	0.01 dB
OPERATING TIME	≥ 130 hours	≥ 130 hours
BATTERY TYPE	(3) AA batteries	(3) AA batteries
DIMENSIONS	7" x 3.25" x 1.5" (17.78 cm x 8.26 cm x 2.54 cm)	7" x 3.25" x 1.5" (17.78 cm x 8.26 cm x 2.54 cm)
WEIGHT	1.50 lb (680 g)	1.50 lb (680 g)
UPC #	811490019089	811490019966

FLS Series Fiber Optic MM / SM Optical Light Source



These optical light sources are the perfect tools for providing a stable light source for multimode or single mode fiber measurements. Features the following:

- Includes FC, SC, and LC adapters to directly connect to UPC/PC FC, SC, and LC fiber connectors
- Highly stable output power and wavelengths
- **FLS-55** Has four different modulation outputs (CW, 270 Hz, 1 kHz, 2 kHz) at 1310 nm and 1550 nm wavelengths
- **FLS-55** Has four different modulation outputs (CW, 270 Hz, 1 kHz, 2 kHz) at 850/1300 nm (multimode) and 1310/1550 nm (singlemode) wavelengths
- Flush button design makes it easy to use and prevents dust from entering the unit
- Shatter-resistant sleeve protects the light source from falls or other damage
- Backlit LCD screen provides a clear display, ideal for dark places
- **FLS-50** Includes: Fiber Optic Light Source (SM), LC Adapter, SC Adapter, (2) Cleaning Swabs, (3) AA Batteries (required for operation), & a Storage Pouch
- **FLS-55** Includes: Fiber Optic Light Source (MM/SM), FC Adapter, LC Adapter, SC Adapter, (2) Cleaning Swabs, (3) AA Batteries (required for operation), & a Storage Pouch

SPECIFICATIONS	FLS-50	FLS-55
FIBER TYPES	Singlemode	Multimode & Singlemode
CONNECTOR TYPES	FC, SC, LC	FC, SC, LC
WAVELENGTHS	1310, 1550	850, 1300, 1310, 1550
TYPICAL OUTPUT POWER	-7 dBm	-7 dBm
OUTPUT STABILITY	± 0.05 dB / 15 min or ± 0.1 dB / 8 hr	± 0.05 dB / 15 min or ± 0.1 dB / 8 hr
OPERATING TEMPERATURE	-10 ± 60°C	-10 ± 60°C
SPECTRAL WIDTH	≤ 10 nm	≤ 10 nm
MODULATION FREQUENCIES	CW / 270 Hz / 1 kHz / 2 kHz	CW / 270 Hz / 1 kHz / 2 kHz
POWER SUPPLY	(3) AA 1.5V alkaline batteries	(3) AA 1.5V alkaline batteries
STORAGE TEMPERATURE	-25 ± 70°C	-25 ± 70°C
DIMENSIONS	7" x 3 3/16" x 1 1/4" (17.78 cm x 8.10 cm x 3.18 cm)	7" x 3 3/16" x 1 1/4" (17.78 cm x 8.10 cm x 3.18 cm)
WEIGHT	0.902 lb (0.409 kg)	0.902 lb (0.409 kg)
UPC #	811490018655	810053350195