

# Marshall Electronics V-LCD17HR

**toner**  
cable equipment, inc.  
www.tonercable.com

**17" Rackmount / Desktop Monitor with 3G-SDI or Dual HD-SDI**



## FEATURES

- 1920 x 1080 resolution
- Budget 17-inch production / rack mount monitor
- False Color Filter
- Thin, robust mechanical design
- Also available with dual input HD-SDI (V-LCD17HR-2HD)
- Available with desktop stands (V-LCD17HR-3G-DT / V-LCD17HR-2HD-DT)



*Shown with desktop stand*

## AVAILABLE MODELS:

- V-LCD17HR-3G (includes rack ears only)
- V-LCD17HR-DVII (includes rack ears only)
- V-LCD17HR-2HD (includes rack ears only)
- V-LCD17HR-2HDI (includes rack ears only)
- V-LCD17HR-3G-DT (includes desktop stand)
- V-LCD17HR-DVII-DT (includes desktop stand)
- V-LCD17HR-2HD-DT (includes desktop stand)
- V-LCD17HR-2HDI-DT (includes desktop stand)



The V-LCD17HR is the perfect display for low-cost production or confidence monitoring. The V-LCD17HR includes a number of features such as Status Display, False Color Filter, Markers, Freeze Function, Color Temperature Presets, RGB Gain / Bias Adjust, Pixel-to-Pixel, Blue Gun, Hard Tally and user-definable function buttons. The V-LCD17HR can be ordered as a standard EIA 19-inch rack mount monitor with attached rack ears that can be angled to provide the user control over viewing angles. A VESA standard 75mm hole pattern also allows custom mounting installations.

Alternately, the V-LCD17HR can be ordered in desktop configurations (V-LCD17HR-3G-DT / V-LCD17HR-2HD-DT).

**17" Rackmount / Desktop Monitor with 3G-SDI or Dual HD-SDI**

<b>Panel</b>	Number of Panels	1
	Panel Size	17.3" Diagonal
	Resolution	1920 x RGB x 1080
	Aspect Ratio	16:9
	Active Area	367.20 x 229.50 mm
	Type	LCD Panel
	Brightness	300 cd/m2
	Contrast	650:1
	Color Gamut	YUV, RGB
	Viewing Angles (CR>=10)	160° x 150°
	Backlight type	LED
	Adjustable Backlight	Yes
	<b>Features</b>	Video Formats
Loss of Input Curtain		Yes
Color Temperature		D65, D55 and D93
Tally		Yes
False Color		Yes
HDMI CSC Auto		With HDMI Module
HDMI Ratio Auto		With HDMI Module
Pixel to Pixel		Yes
Pre-set Gamma points		Yes
Self-Sensing		Yes
Modular Input Slot		1
Re-clocked/Re-Shaped		Yes
<b>Video Input</b>	3G-HDSDI	Optional
	Dual HDSDI	Optional
	HDMI Dual	Optional
	DVI-I	Optional
	Optical	Optional
<b>Video Output</b>	3G-HDSDI	Yes
	Input Status Display	Yes
<b>Control Inputs</b>	Tally	Yes
<b>Mechanical</b>	Controls on front Panel	Yes
	User-Defined Function Buttons	Yes
	Pivot Angle	Yes
	Handles	Yes
<b>Power</b>	Voltage	12 VDC
	Consumption	3.5A @ 12VDC (42 W)
	Power Switch	Yes
	Connector	2-Pin Twist Lock
<b>Compliance</b>	Compliance	CE approved
<b>Environmental</b>	Operating Temperature (C°)	32°F to 104°F
	Storage Temperature (C°)	-4°F to 120°F
	Rack Unit dimensions	18.85"W x 10.40"H x 1.1"D
	Weight (Main Body)	8.8 lbs
	Vesa Mount Pattern	75mm