



MG7315

8x4 343 Mbps + N450 WiFi Cable Modem

The Motorola Model MG7315 cable modem with built-in router supports modem speeds up to 343 Mbps. With its high speed and IPv4 and IPv6 networking support, this is a product designed and built for use today and for years to come. The embedded N450 3x3 wireless router provides the range, wireless speeds and networking support needed for multimedia, Internet video and high-performance networking in a home or office. Power Boost technology amplifies the wireless signal to the legal limit in the U.S.

Package Contents

- Cable Modem • Power Cube • Ethernet Cable
- Velcro® Cable Organizer • Coax Connection Tool
- Quick Start Flyer



Features

Fast data speed – Up to 343 Mbps downstream and 123 Mbps upstream with bonding of up to eight channels downstream and four channels upstream. Full-Band Capture Digital Tuning lets service providers deliver faster, more reliable Internet.

High speed 3x3 N450 Wi-Fi Router

- N450 Wi-Fi plus 4 Gigabit Ethernet ports
- N450 3x3 Wi-Fi provides wireless Internet access for wireless n, ac, g, and b devices including smartphones, computers, tablets, and HDTVs
- Wireless Power Boost to the FCC limit for extended speed and range
- Four 10/100/1000 Gigabit Ethernet ports for wired connection to computers, HDTVs, game stations, and other Ethernet-capable devices

Security and Safety Features

- Advanced Firewall with DoS (Denial-of-Service) attack prevention, plus double SPI and NAT firewall protection
- Guest network access gives visitors Internet services while protecting your local network's information
- Parental control lets parents restrict access to child-inappropriate Web sites
- Browser-based Configuration Manager with easy menus and context-sensitive help

Easy installation

Supports IPv4 and IPv6 – Support for the latest Internet addressing keeps your equipment current.

Ten status-reporting LEDs – Power, Downstream, Upstream, Online, LAN (1-4), Wireless, and WPS lights allow easy status monitoring.

DOCSIS 3.0 compatible, and compatible with earlier standards – Provides support for the latest data-over-cable standard DOCSIS 3.0, as well as DOCSIS 1.1 and 2.0, to ensure operation and compatibility with all U.S. operators. DOCSIS (Data Over Cable Service Interface Specification) is the industry standard for transmission of Internet data over cable-based systems in the U.S. and many other countries.

SNMP v1/v2/v3

Compact, space-saving design

Experienced, U.S.-based technical support

Certified by CableLabs®, Comcast XFINITY®, Time Warner Cable®, and other service providers

Two year warranty

MG7315

8x4 343 Mbps + N450 WiFi Cable Modem

Specifications

General

Cable Modem Service Interface:	F-type female 75 Ω (standard coaxial connector)	
Ethernet LAN Interface:	4 X RJ-45 10/100/1000 Mbps Ethernet, with Auto-MDI/MDIX	
Wireless:	802.11n/g/b, 3x3 MIMO (Multiple Input Multiple Output)	
Router Mode:	<ul style="list-style-type: none">• Dynamic DNS• DHCP Server and Client• NAT• Bridging	<ul style="list-style-type: none">• Port Forwarding/DMZ support• RIP V1 and V2• Support for up to 253 client devices
Security:	<ul style="list-style-type: none">• Stateful Packet Inspection (SPI)• VPN passthrough: PPTP, IPsec tunneling• Parental Control• Attack Protection• Password protected system management	<ul style="list-style-type: none">• IP/MAC/Port filtering• Denial of Service Notification• Wireless MAC address filtering• Supports Baseline Encryption (BPI) Management• Cable modem diagnostic log
Wireless Networking and Security:	<ul style="list-style-type: none">• Compliant with IEEE 802.11n, g, and, b standards• Up to 450 Mbps wireless data rate**• 3x3 Transmit/Receive, MIMO• Power Boost wireless amplifiers• 2.4 GHz - 2.484 GHz frequency range• WDS• WMM/WME• WPA-PSK/WPA2-PSK	<ul style="list-style-type: none">• WPA/WPA2• WEP-64/128• TKIP/AES• WPS• 802.1x Authentication• 8 SSIDs• Wireless Quality of Service• Transmit power: 20dBm• Three internal antennas
Status Indicators:	Power, Downstream link, Upstream link, Connection status, Ethernet link (1-4), Wireless link, WPS	
Size:	8.6" H x 9.1" D x 2.6" W (218mm x 231mm x 66mm)	
Weight:	21.6 ounces (602 grams)	
Power Adapter:	DoE-compliant Level VI energy-saving, UL-listed power adapter with 12 Volt DC, 2 Amp output and 100-240VAC universal input. NEMA 1-15 (North American style) 2-prong plug is provided in the US.	
Operating Temperature:	32° to 104° F (0° to 40° C)	
Certifications:	FCC 15B and 15C, FCC MPE, Bureau Veritas 60950-1 ITE safety, Wi-Fi Alliance®, CableLabs®, cable service providers	
Surge Protection:	Ruggedized cable and power lightning protection	
Warranty:	Two years	



MG7513

8x4 343 Mbps + N450 WiFi Cable Modem

Specifications

Operating Parameters

Downstream:

Data Rate*:	Up to 343 Mbps (8 channels), Up to 43 Mbps (single channel)
Frequency:	88 to 1002 MHz (edge to edge)
Modulation:	64 or 256 QAM
Operating Level Range:	-15 to +15 dBmV

Upstream:

Data Rate*:	Up to 123 Mbps (4 channels), Up to 31 Mbps (single channel)
Frequency:	5 to 42 MHz (edge to edge)
Modulation:	QPSK, 8QAM, 16QAM, 32QAM, 64QAM, 128QAM, 256QAM
Operating Level Range:	A-TDMA: +8 to +54 dBmV (32QAM, 64QAM) +8 to +58 dBmV (QPSK) S-CDMA: +8 to +53 dBmV (all modulations)

Security:	DOCSIS 3.0 Security (BPI+, EAE, SSD)
Network Protocols:	IPv4, IPv6, TCP, UDP, ARP, ICMP, DHCP, FTP, TFTP, SNMP, HTTP
Application Protocol:	SNMP v1/v2/v3
DHCP Client:	Automatically retrieves IP and DNS server address from DHCP server at ISP
ToD (RF868):	ToD support for local and MSO time synchronization
TFTP Client:	TFTP support for cable modem configuration file download
Management:	Web-based management interface utility
Core Chipset:	Broadcom BCM3383G