

EX6XL Universal Compression Connector

Installers are faced with the problem of identifying old unmarked 60% through Quad Shield Series 6 cable, and having to guess which connector is the best match. This results in unnecessary service calls due to the use of the wrong connector/cable match.

The unique patented design of the EX® body achieves true universality on 60% through Quad Shield for PE, and PVC jackets.



Specifications	
Bandwidth	0 MHz to 3 GHz
Impedance	75 Ohms (nominal)
Return Loss	Minimum -30 dB to 3 GHz
Insertion Loss	Less than .10 dB to 3 GHz
Operating Voltage	90 V (at 60 Hz continuous AC)
Operating Temperature	-40o F to + 140o F (-40o C to 60o C)
Cable Retention	45 lbs (20.41 kg) minimum
<i>Meets or Exceeds all SCTE Specifications</i>	

Part Numbers	
PPC-EX6XL-NBN	EX® Universal compression connector, extended body, series 6 cable

Preparation & Installation Tools			
Compression Tool	CATAS, VT200 (for use w/ XL series)		
	CAT-AS-EX, VT300 (for use w/ EX series)		
1/4" - 1/4" universal drop cable preparation tool	LDT596-250	DDT59611	
	7/16" snap torque wrench	TW207	TW307

Features

