



HD-2

High-Definition MPEG-2/4 QAM Set-Top Box With CAS



Description

Part of Pico Digital's all-digital CONDOR solution, the **HD-2** HD QAM set-top box descrambles signals from the CONDOR headend while converting digital signals to analog for display on legacy TVs. Featuring HDMI and composite outputs, the unit offers PVR/media player capabilities, Electronic Program Guide (EPG) support, and an intuitive high-definition interface for ease of use. The **HD-2** can be deployed as a stand-alone solution for non-encrypted clear QAM applications.

Features

- Decodes high-definition and standard-definition signals
- Decodes MPEG-2 / AVC / H.264 / MPEG-4 video
- Decodes MPEG-1 Layer I/II
- Clear QAM and Hollywood-approved CAS
- Supports 64 and 256 QAM inputs
- Elegant, intuitive, and simple high-definition user interface
- Auto scanning for QAM channels and programs
- Supports Electronic Program Guide (EPG)
- Multiple language support
- Firmware updates via cable TV network
- HDMI® and analog composite video/audio outputs
- PVR via two external USB sticks/drives
- Optical SPDIF
- Universal remote control included

Subscriber Experience



The InfoBar is similar to a traditional program Now and Next bar, which is displayed on channel change or when the user requests.



The easy-to-use program guide shows what's on TV and allows users to easily bring up detailed information about programs of interest.

HD-2

High-Definition MPEG-2/4 QAM Set-Top Box With CAS

Specification

Tuner

QAM Modes	ITU-T J.83, Annex B
Constellation	64/256 QAM
Frequency Range	54 MHz ~ 862 MHz
Bandwidth	6 MHz
Input Impedance	75 Ω
Input Level Range	-15 dBmV ~ 30 dBmV
Signal Input	IEC 169-24, F-Type, female
Symbol Rate	7.252 Msps max.

Video

MPEG Decoder	MPEG-2/MPEG-4/H.264
Video Resolution	1080P(HD), 720p(HD), 480i(SD)
Aspect Ratio	4:3, 16:9

Audio

MPEG Decoder	MPEG-1 Layer 1/2
Output	Stereo/right/left/mono
Sampling Frequency	32 kHz, 44.1 kHz, 48 kHz

Security

Conditional Access	Hollywood-approved CAS
--------------------	------------------------

Front Panel

KEY	3 keys (Standby, CH-, CH+)
LED	Red: Power/standby Green: Signal
USB	USB 2.0
CA Card	1 slot

Rear Panel

RF Input	F-Type
Composite Output	3 RCA (CVBS, A. left, A. right)
Digital Audio	S/PDIF optical
HDMI	19 pin female
USB	USB 2.0
DC Input	12 V/1.5 A

Remote Control

Batteries	2 AAA type
-----------	------------

Power Supply

Power supply mode	External
Plug Type	American standard
AC Input (V/Hz)	AC 110 V ~ 240 V, 50 Hz/60 Hz
Output Voltage (V)	12 V

General

Dimensions	5.15" (L) x 6.70" (D) x 1.50" (H)
Weight	Net 4 lb.
Operating Temperature	0°C ~ 40°C
Consumption	18 W max.
Standby Consumption	1 W
RoHs Compliant	



Ordering Information

HD-2 High-Definition MPEG-2/4 QAM Set-Top Box With CAS