



MRD2600

Modular Receiver



The MRD 2600 receiver shares the professional-grade front-end collection from Sencore's newest decoder designs, but removes the baseband video and audio components. This makes it a cost-effective solution for single-transponder, multi-service descrambling or single channel digital turnaround applications.

With available satellite, terrestrial (8VSB, QAM-B, DVB-T/T2/C/C2/ISDB-T), ASI, and IP input modules, in conjunction with dual-CAM DVB-CI and BISS descrambling, the MRD 2600 is ideally suited for transport stream input/output. The product is a perfect to feed internal IP distribution or front transcode infrastructure which is missing critical RF interfaces, especially where density is not a key requirement.

The MRD 2600 provides a wide range of control options, including full configuration and status through the front panel and a clean, easy-to-use web GUI. It also features a full SNMP interface, including configurable traps on alarms for easy integration into a control system, and as with all Sencore products, Sencore's professional support team is just a phone call away in the unlikely event that questions should arise.

KEY FEATURES

- Built-in ASI I/O for maximum value and flexibility
- Available IP and RF satellite I/O modules:
 - √ 8VSB/QAM-B receiver designed for A74
 - √ DVB-T/T2/C/C2/ISDB-T receiver
 - √ TurboPSK Interface with full mode support
 - √ IP Interface with redundant receive paths
 - √ Dual, mirrored TS over IP transmission
- Flexible descrambling support
 - √ Two DVB-CI Interfaces supporting up to 100Mbps
 - √ Flexible per-PID/service configuration
 - √ Built-in BISS Mode 1, Mode E and multi-key
 - √ Up to 12 Independent BISS keys supported
- Easy-to-use web interface
- Full control, status, and alarm monitoring via SNMP

APPLICATIONS

- **Multi-Service DVB-CI Decryption**
Downlink a DVB-S/S2/S2X transponder, descramble with up to two professional DVB-CI CAMs, and output an IP MPTS to downstream transcoders or decoders.
- **8VSB Reception and Turnaround**
Receive local stations and output for backhaul as ASI and IP. 8VSB input interface designed for strenuous A74 reception conditions.
- **Satellite Reception and BISS Descrambling**
Simple solution for BISS, BISS-E, or Multi-BISS decryption. Transmit transport stream in the clear via ASI or IP for additional processing.

MRD2600

Modular Receiver

BASE UNIT FEATURES

MRD 26000

ASI Input: 1x 75Ω BNC
ASI Output: 1x 75Ω BNC
Supported Bitrate: 250 Kbps to 200 Mbps

BISS Descrambling License MRD 26921
Supported Modes: Mode 1, Mode E, Injected ID
Multi-BISS Support: Up to 12 Separate Keys

DVB-CI Multi-Service MRD 26991
With DVB-CI Module: Enables Multi-service Descrambling

PID/Service Filtering License MRD 26928
Filtering: 10 Independent TS (MPTS or SPTS) created; output via IP or ASI

Table Regeneration (DVB Mode): PAT regeneration
Table Pass-through (DVB Mode): PMT, CAT, NIT pass-through Table
Regeneration (DVB Mode): PAT, SDT
Table Pass-through (DVB Mode): PMT, CAT, NIT, EIT, RST, TDT, TOT

DVB-CI DESCRAMBLING MODULE

MRD 421

Physical Interface: Adds two DVB-CI CAM Slots
Without Multi-Service License: Descrambles Decoded Service Only
With Multi-Service License: Number of Services limited by CAM

IP INPUT/OUTPUT MODULE

MRD 127

Physical Interface: 2x RJ45, 10/100/1000 Auto-Negotiate
Input Format: UDP or RTP

Constant Bitrate or Null-Stripped
RTP Header Extensions Supported
SMPTE 2022/CoP3 FEC Supported
UDP

Output Format:
MPE De-encapsulation: Up to 2 PIDs
Up to 60Mbps per MPE PID
IP Encapsulation: 1 to 7 TS Packets per IP Packet
Addressing: Unicast or Multicast
IGMP compatibility: Version 1, 2 & 3
Per TS Bitrate: 250 Kbps to 200 Mbps

MPEG/IP FEC Output License MRD 26925
Additional Output Formats: RTP and Header Extensions
SMPTE 2022/CoP3 FEC Supported

DVB-S/S2 INPUT MODULE

MRD 116

Physical Interface: 4x 75Ω F-Type
Frequency Range: 950-2150 MHz
Symbol Rates: 1-45 MSps
DVB-S Modulation Modes: QPSK (All FEC Rates)
DVB-S2 Modulation Modes: QPSK/8PSK (All FEC Rates)
16/32APSK (with License)
LNB Power: Off/13/14/18/19VDC @ 450mA
Control Tone Support: 22 kHz On/Off
Supported Roll-off Factors: 0.35, 0.25, 0.20, 0.15, 0.10, 0.05

DVB-S2 Advanced Feature License MRD 26916
Additional Modulation Modes: 16/32/64APSK (All FEC Rates)
VCM Demodulation Support
Multistream Support (Single ISI)

DVB-S/S2/S2X INPUT MODULE

MRD 116A

Physical Interface: 4x 75Ω F-Type
Frequency Range: 950-2150 MHz
Symbol Rates: 1-72 MSps with 8PSK/QPSK
1-60 Msps with 16APSK and higher
QPSK (All FEC Rates)
DVB-S Modulation Modes: QPSK (All FEC Rates)
DVB-S2/S2X Modulation Modes: QPSK/8PSK (All FEC Rates)
16/32/64APSK (with License)
LNB Power: Off/13/14/18/19VDC @ 450mA
Control Tone Support: 22 kHz On/Off
Supported Roll-off Factors: 0.35, 0.25, 0.20, 0.15, 0.10, 0.05

DVB-S2/S2X Advanced Feature License MRD 26916
Additional Modulation Modes: 16/32/64APSK (All FEC Rates)
VCM Demodulation Support
Multistream Support (Single ISI)

8VSB/QAM-B INPUT MODULE

MRD 101

Physical Interface: 1x 75Ω F-Type
Frequency Range: 50-1000 MHz
Sensitivity: -34 to +40 dBmV (A74 Compliant)

8VSB Standard: ATSC A/53E
8VSB Channel Plans: Broadcast

QAM Standard: ITU Annex B/SCTE DVS-031
QAM Channel Plans: FCC, IRC, HRC
QAM Constellations: QAM64, QAM256

BROADCOM TURBOPSK INPUT MODULE

MRD 111

Physical Interface: 1x 75Ω F-Type
Frequency Range: 950-2150 MHz
Symbol Rates: 1-30 MSps
DVB-S Modulation Modes: QPSK (All FEC Rates)
TurboPSK Modulation Modes: QPSK /8PSK (All FEC Rates)

DVB-T/T2/C/C2/ISDB-T INPUT MODULE

MRD 115

Physical Interface: 1x 75Ω F-Type
Frequency Range: 42-1002 MHz
Bandwidth: 1.7MHz, 5 MHz, 6MHz, 7MHz, 8MHz
Constellations:
DVB-T: QPSK, QAM16, QAM64 (All FEC Rates)
DVB-T2: QPSK, QAM16, QAM64, QAM256 (All FEC Rates)
DVB-C: QAM16, QAM32, QAM64, QAM128, QAM256 (All FEC Rates)
DVB-C2: QAM16, QAM64, QAM256, QAM1024, QAM4096 (All FEC Rates)
ISDB-T: QPSK, QAM16, QAM64 (All FEC Rates)

MANAGEMENT

Connector: RJ-45 10/100 - Auto Negotiating
Protocols: HTTP and SNMP
User Interfaces: Full control via web GUI
Full control via front panel
Full status and control via SNMP
Automation Interfaces: Configurable SNMP traps
Web services API available
Syslog message logging
Firmware Updates: Via Web GUI



MRD2600

Modular Receiver

DIMENSIONS/POWER

| | |
|-----------------|---|
| Height: | 1 RU, 1.72" (44 mm) |
| Width: | 1 RU, 17.2" (437 mm) |
| Depth: | 14.6" (370 mm) |
| Power: | 100-240 VAC 50/60 Hz 36-72 VDC |
| Supply Options: | Single AC Power Supply (Standard) Dual AC Power Supply Single DC Power Supply |

ENVIRONMENTAL CONDITIONS

| | |
|------------------------------|-----------------------|
| Operating Temp: | 0° to 45°C |
| Storage Temp: | -40°C to 65°C |
| Relative Operating Humidity: | <95% (non-condensing) |