

## PS-60/90-15-I

### CATV Ferroresonant Power Supply (International)

120/240 VAC SWITCHABLE INPUT  
 60/90 VAC SWITCHABLE OUTPUT

**TYPE** Non-Standby Power Supply  
**MODEL** PS-60/90-15-I 50 Hz (International)

#### 1) ELECTRONICS

Maximum Output Power	(VA)	900
Nominal Input Voltage	(VAC) ±15%	120/230 (Switchable)
Input Frequency	(Hz)	50
Input Protection (Fuse)	(A)	8
Output Voltage	(V)± 5%	60/90 (Switchable)
Output Frequency	(Hz)	50
Maximum Output Current	(A)	15
Suggested minimum load	(A)	1

#### 2) INDICATORS

Output voltage indicator Green LED

#### 3) VARIOUS

Lock	Standard Key
Water proof	NEMA IP21
Mounting system	Powder Coat Wall or Pole
Color	Powder Coat Champagne
Flange Fitting	5/8-24 CH Type
Protection	Short Circuit and Alarm
Circuit Breaker	Micro

#### 4) DIMENSIONS & WEIGHT

Height	13.1 inches	333 mm
Wide	8.4 inches	214 mm
Deep	7.2 inches	182 mm
Weight	43 lbs	19.5 Kg

