

PS-60/90-6D CATV Ferroresonant Power Supply (Domestic)

120/240 VAC SWITCHABLE INPUT
60/90 VAC SWITCHABLE OUTPUT

TYPE Non-Standby Power Supply
MODEL PS-60/90-6D 60 Hz (Domestic)

1) ELECTRONICS

| | | |
|-------------------------|------------|-----------------------------|
| Maximum Output Power | (VA) | 360 |
| Nominal Input Voltage | (VAC) ±15% | 120/230 (Switchable) |
| Input Frequency | (Hz) | 60 |
| Input Protection (Fuse) | (A) | 8 |
| Output Voltage | (V)± 5% | 60/90 (Switchable) |
| Output Frequency | (Hz) | 60 |
| Maximum Output Current | (A) | 6 |
| Suggested minimum load | (A) | 1 |

2) INDICATORS

Output voltage indicator Green LED

3) VARIOUS

| | |
|-----------------|--------------------------|
| Lock | Standard Key |
| Water proof | NEMA IP21 |
| Mounting system | Powder Coat Wall or Pole |
| Color | Powder Coat Champagne |
| Flange Fitting | 5/8-24 CH Type |
| Protection | Short Circuit and Alarm |
| Circuit Breaker | Micro |

4) DIMENSIONS & WEIGHT

| | | |
|--------|-------------|---------|
| Height | 13.1 inches | 333 mm |
| Wide | 8.4 inches | 214 mm |
| Deep | 7.2 inches | 182 mm |
| Weight | 24 lbs | 10.5 Kg |

