



# 5341

## DOCSIS3.0 Cable Modem/Router

The Zoom Model 5341 cable modem meets the cable industry's DOCSIS 3.0 standard for speeds up to 343 Mbps, and also works with lower-speed DOCSIS 2.0 and 1.1 services. And with IPv4 and IPv6 networking support, this is a product designed and built for use today and for years to come. The Model 5341 has been tested and certified by CableLabs to work with nearly all U.S. cable services.

This modem can be plugged into any Windows, Macintosh or Linux computer with an Ethernet port. The Model 5341 can also be plugged into routers and routers with wireless capability for sharing of your high-speed service with multiple devices. With its easy installation, high speed, and broad capability, the Model 5341 is the perfect choice for almost any cable modem user.



### Features:

- **Easy Installation**

- **Fast data speeds**

Up to 343 Mbps downstream and 123 Mbps upstream with bonding of up to eight channels on downloads and four channels on uploads

- **Fast 10/100/1000Base-T Ethernet connectivity**

To support the very fast DOCSIS 3.0 data transfers and provide compatibility and easy installation with almost any Windows, Mac or Linux computer, as well as both wired and wireless routers

- **Supports IPv4 and IPv6**

Support for the future of Internet addressing keeps your equipment current

- **Five status-reporting LEDs**

Power, Downstream, Upstream, Status, and Link lights allow easy status monitoring.

- **DOCSIS 3.0 compatible, as well as earlier standards**

Provides support for the latest data-over cable standard DOCSIS 3.0, as well as DOCSIS 1.1 and 2.0 to ensure operation with the fastest available services and compatibility with all US operators.

DOCSIS (Data Over Cable Service Interface Specification) is the industry standard for transmission of Internet data over cable-based systems in the US and many other countries. Check with your service provider to ensure they use the DOCSIS standard.

- **Extensive SNMP management support**

Includes MIB-II, Ethernet - Like MIB, Bridge MIB, Cable Device MIB, Baseline Privacy Interface MIB, RF Interface MIB

- **Flexible Cable Modem Orientation**-Horizontal or vertical using the 5341Modem Stand

- **Experienced, U.S.-based technical support for both consumers and service providers**

- **Certified by CableLabs**

- **Two year warranty**

## DOCSIS3.0 Cable Modem/Router

### Specifications

Cable modem service interface	F-type female 75 Ω (standard coaxial connector)
Ethernet LAN interface	RJ-45 10/100/1000 Mbps Ethernet, with Auto-MDI/MDIX
Status Indicators	Power, Downstream link, Upstream link, Ethernet link, Connection Status
Size	6.3 X 4.9 X 1.3 inches (16 X 12.4 X 3.3cm)
Weight	8.7 ounces (246 grams)
Power adapter	Level 4 energy-saving, switching power supply with 12 Volt DC, 1 Amp output
Operating temperature	32° to 104° F (0° to 40°C)
System Requirements	- The cable modem must be connected to a cable modem service that uses any of the DOCSIS standards - 3.0, 2.0, 1.1 - An available Ethernet port on a Windows, Macintosh, or Linux computer, or an available Ethernet port on a wired or wireless router.
Approvals	FCC part 15B, US safety (BV), CE, CableLabs®

### Operating Parameters

	Downstream	Upstream
Data Rate*	Up to 343 Mbps (8 channels) Up to 43 (single channel)	Up to 123 Mbps (4 channels) Up to 31 Mbps (single channel)
Frequency	88 to 866 MHz (edge to edge)	5 to 85 MHz (edge to edge)
Modulation	64 or 256 QAM	QPSK, 8QAM, 16QAM, 32QAM, 64QAM, 128QAM, 256QAM

Frequency search cache	4 entries
Frequency search channel plan	6 MHz step
Security	DOCSIS 3.0 Security (BPI+, EAE, SSD)
Bandwidth	DOCSIS 2.0 TDMA: 200, 400, 800, 1600, 3200, 6400 KHz S-CDMA: 1600, 3200, 6400 KHz DOCSIS 3.0 TDMA: 1600, 3200, 6400 KHz S-CDMA: 1600, 3200, 6400 KHz
Maximum Number of CPEs	32 MAC addresses
Network Protocol	Network protocols: IP / TCP / UDP / ARP / ICMP /DHCP / TP / TFTP / SNMP / HTTP Application protocol: SNMP v1/v2/v3 DHCP client: Automatically retrieves IP and DNS server address from DHCP server at ISP ToD (RF868): ToD support for local and MSO time synchronization TFTP Client: TFTP support for cable modem configuration file download Management Web-based management interface utility
Core chipset	Broadcom BCM3382DKFBG

### Package contents:

- Cable Modem
- Modem Stand
- Power Cube
- Ethernet Cable
- Quick Start Flyer

\* Data throughput will be reduced by network overhead. Delivered data speeds are also dependent upon the configuration and capacity of the data-over-cable service on which the 5341 is used.