



CompactCG HD

Compact & Portable Broadcast Graphics

Priced with the attractive affordability the industry has come to expect from Compix, the CompactCG HD is ideal for channel branding, with software options including NewsScroll with RSS, which provides the power of multiple crawls, logos, a real-time clock, live weather updates, ratings, and live RSS feeds, among other elements. The system's small footprint makes it a perfect fit for mobile broadcast and OB vans, fly pack systems, and multivenuue use. Also available is AutoCast, a powerful software package that lets you generate, then automate graphic playlists. With an elegant, intuitive interface for creating broadcast-quality graphics, the CompactCG HD also serves as a convenient and familiar solution in the rental market.



Features

- Uses same applications as full sized systems
- Broadcast quality video
- Active video input bypass relay
- Icon-based drag-and-drop tools
- 260+ effects including roll, crawl and reveals
- Multilingual support using Windows IME
- Logo generation with optional NewsScroll software with RSS feeds
- Automation and third-party interface capable via optional AutoCast application.
- Pre-assembled, pre-configured turnkey systems
- Free offline graphics license with registration

Specifications

Basic Configuration

The CompactCG HD configuration is a single SDI HD-SD capable channel. SD-SDI passes VBI, HD-SDI passes HANC and VANC.

Video I/O

Input	1 SDI HD-SD Video In (can also serve as source genlock input)
Outputs	1 SDI HD-SD Video, 1 SDI HD-SD Key
Connector Type	All BNC for input and output
Impedance	75 ohms
Formats	SD-SDI HD-SDI 525/625

Audio

The CompactCG HD provides embedded audio pass-through. 16, 20 and 24 bit streams are supported. 48 kHz sampling frequency.

Inputs	Video input
Outputs	Up to 8 SDI embedded channels
Type	BNC

Chassis 1RU

Height	1.75" / 4.45cm
Width	19" / 48.26 cm
Depth	15" / 38.1 cm
Weight	20lbs / 9kg

System Specifications

Windows 7
Intel Core 2 Duo 2.8Ghz Processor
2GB DDR-RAM
HD-SD SDI Video I/O board
Integrated onboard graphics
160 GB SATA HDD (5400 RPM)
DVD±RW drive
6 USB 2.0 ports (rear)
USB PC keyboard
PS/2 mouse
Two RJ-45 Gigabit Ethernet ports
Front USB 2.0 port

Options

Mechanical bypass relay
GenCG RCES offline additional licenses
CompixMOS newsroom solution
NewsScroll RSS channel branding solution
AutoCast automated graphic data entry and playback via Ethernet or serial connections
Compix QuickShot portable add-on package
Compix SchoolSmart education add-on package
Compix Spirit faith add-on package
Interface to various third party products

Power

250W AC power supply with Power Factor Correction (PFC)
100-240VAC, 50/60Hz, Auto sensing