

# PONA 3000 Series

## Erbium Doped Fiber Amplifier

### APPLICATIONS

- High Performance Supertrunking Links
- High Power Distribution Networks
- Fiber Deep Architectures
- FTTx Networks

### FEATURES


- Full Function High Power Fiber Optic Amplifier Ready for Integration
- Low Noise Figure (Typ < 6 dB)
- Total Input Power Range: -10 dBm to +12 dBm
- Total Output Power: +27 dBm to +35 dBm (Optical Output Power Splitter is Optional For These Units)
- Standard RS-232 Communications
- Low Electrical Power Consumption
- Input / Output Isolation > 40/40 dB
- Polarization Dependant Gain < 0.1 dB
- Polarization Mode Dispersion < 0.5 ps



The EMCORE PONA 3000 Series Fiber Optical Amplifier Module is an ideal building block for OEM system integrators. The family of PONA 3000 Optical Amplifiers is designed to meet the most demanding noise performance requirements of CATV and FTTx applications, and performs all the functions required of an optical amplifier for system integration. Packaged in a convenient 2RU housing, the PONA 3000 series optical amplifiers provide optical isolation on the input and output of the gain block for stable, low noise operation. The input and output optical signal power levels are detected for monitoring and control. The input optical signal is amplified with active gain control for a constant output power level, or with active output power control for constant gain mode. The PONA 3000 series optical amplifiers also provide monitoring functions and associated alarms for all vital characteristics. The optical output of the PONA 3000 series optical amplifiers can be split into a number of ports by an optional internal splitter.

PONA3000 series includes AC/DC power supply, front panel, optical splitters, network card and all necessary connectors.

### Sample FTTx Architecture



## PONA 3000 Series Erbium Doped Fiber Amplifier

### SPECIFICATIONS

PROPERTY	UNIT	LIMIT	PONA MODELS				COMMENT
Product Code			3027	3030	3032	3035	
PERFORMANCE							(note 1)
Operating Input Power	Pin (dBm)	Max	+12	+12	+12	+12	
Operating Input Power	Pin (dBm)	Min	-10	-10	-10	-10	
Output Power	Po (dBm)		27.0	30.0	32.0	35.0	Nominal (note 2)
Noise Figure	NF (dB)	Typ/Max	5.5/6.0	5.5/6.0	5.5/6.0	5.5/6.0	(note 3)
Static Gain Flatness	GF (dB)	Max	+/-1.0	+/-1.0	+/-1.0	+/-1.0	(note 4)
Dynamic Gain Flatness	(dB)	Max	+/-2.00	+/-2.00	+/-2.25	+/-2.50	(note 5)
Output Power Stability	(dB)	Max	+/- 0.25	+/- 0.25	+/-0.25	+/- 0.25	(note 6)
Power Consumption (steady state regime)	Psys (W)	Max	40 25	50 30	65 40	80 50	50°C Case (premium) 50°C Case (economy) (note7)
Remnant pump power to output	Prp (dBm)	Nom.	<-30	<-30	<-30	<-30	

Notes:

- 1) Unless stated otherwise all specifications apply over the full temperature range and humidity
- 2) Depending on the fiber optic patchcord interface the measured value can vary up to 0.5 dB less than the actual value
- 3) Measured @ 25°C, EPin = 0 dBm
- 4) Measured with a swept Probe Signal (Pp), where Pp = 0 dBm @ 25°C
- 5) Measured with a swept Probe Signal (Pp), and a fixed Tone Signal (Pt) @ 1553nm; (Pt = Pp+20 dB; Pt + Pp = 0 dBm) @ 25°C
- 6) Stability over polarization and temperature
- 7) Premium version – PONA with cooled, Telcordia qualified pumps  
Economy version – PONA with uncooled pumps

### PHYSICAL

GENERAL PROPERTY	REQUIREMENT	COMMENTS
Operating Wavelength	1545 ~ 1562nm	Standard
Operating Case Temperature	0°C to 50°C	Standard
Storage Temperature	-40°C to 85°C	Standard
Operating Humidity	20% to 85%	Non-condensing
Voltage Supply Range	85 VAC to 265 VAC 50/60 Hz  -36 to -60 V DC	AC version  DC version  *(Redundant Power Supply is Available by Customer Request)
Optical Connectors	See ordering information	User Specified
Dimensions In Inches	19.0"W x 15.7"D x 3.44"H	19" Rack Mounted, 2 RU