

NeXgen Gateway NXG-CQAM-24 ClearQAM Input Module



The **NXG-CQAM-24 (ClearQAM Input Module)** is part of the Blonder Tongue NeXgen Gateway (NXG) platform that processes HD and SD programs from a Cable or Telco TV service provider.

The **NXG-CQAM-24** input module includes multiple full-band-capture QAM tuners to provide ingest of up to *twenty-four* programs from the incoming cable system.

The **NXG-CQAM-24** module is capable of tuning any *twenty-four* "clear QAM input" channels from 54 to 1002 MHz.

Features

- Supports 24 programs per module
- Supports 54 to 1002 MHz frequency range

Input

QAM	Connector: 1x "F" Female Standards: ITU-T J.83 (64 and 256 QAM) Tuning Range: CATV (54-1002 MHz) Symbol Rate: 5.3606 Msymbols/sec (QAM 256); 5.057 Msymbols/sec (QAM 64) - Auto Detect Bandwidth: 6 MHz QAM Power Level: -15 to +20 dBmV Return Loss: 12 dB Impedance: 75 Ω
------------	---

General

Dimensions (W x D x H):	1.15 x 15.5 x 7.0 inches (29 x 394 x 178 mm)
Power:	Via NXG Mainframe Backplane
Power Consumption:	16 W
Weight:	2.0 lbs (0.9 kg)
Operating Temperature:	32 to 122 °F (0 to 50 °C)
Storage Temperature:	-13 to 158 °F (-25 to 70 °C)
Operating/Storage Humidity:	0 to 95% RH @ 35 °C max, non-condensation

Alarms & Monitoring

Front Panel Indicator:	1x Status LED (Green)
-------------------------------	-----------------------

Ordering Information

Model	Stock #	Description
NXG-CQAM-24	6777	ClearQAM Input Module - 24 Program Capacity