Marshall Electronics V-R35P-SDI



3.5" Ten LCD Screen Rack Mountable Panel with SDI Inputs & Audo NTSC/PAL Detection

The **V-R35P-SDI** is a rack mounted unit that has ten 3.5" active matrix LCD panels and accepts SDI inputs (ITU-R601) with reclocked loop-through capability. This unit has a unique feature that allows the unit to tilt up or down for optimum viewing angle. The unit fits in an EIA standard 19" rack -- three rack spaces high. Each of the ten screens has auto-signal recognition and auto PAL/NTSC recognition built-in. A blue screen will appear in the event of a signal loss. The V-R35P-SDI comes complete with a power supply.

- High Resolution 320 × 234 pixels
- Self-Terminated SDI Inputs with active loop-through
- Automatic NTSC/PAL Video Signal Detection screen
- 90 degree tilt adjustment while mounted in rack





Panel	Number of Panels	10
	Panel Size	3.5"
	Resolution	320 H × 234 V
	Aspect Ratio	3:2
	Active Area	71.6 mm x 52.65 mm
	Туре	LCD Panel
	Brightness	250
	Color Gamut	YUV, RGB
	Backlight type	LED
Features	Video Formats	SD-SDI
	Loss of Input Curtain	Yes
	Color Temperature	D65
	Self-Sensing	Yes
	Re-clocked/Re-Shaped	Yes
Input Connectors	CVBS	No
	YPbPr	No
	SD-SDI	Yes
Output Connectors	CVBS	No
	YpbPr	No
	SD-SDI	Yes
	Input Status Display	Yes
	Pivot Angle	Yes
	Handles/Rack Ears	Yes
	Consumption	12 VDC, 3.0 Amps
Power	Power Switch	Yes
	Connecter	2 pin twist lock
Compliance	Compliance	CE approved
Environmental	Operating Temperature (C°)	32° F to 104° F
Environmental	Storage Temperature (C°)	-14° F to140° F
Environmentai	Storage Temperature (C°) Rack Unit dimensions	-14° F to140° F 18.96"W × 5.2"H × 2.5"D

Specifications Subject To Change Without Notice

Rev 02-17

©Toner Cable Equipment, Inc.