




HGA G!&% \$L !%* A

F UW!A ci bhYX`&I` %*` GUY`~]hY`A i` hgk]hW



Features

- Wide frequency range 950 to 2150 MHz
- 3 Inport Simple interface design provides 2 satellite polarity inputs and 16 outputs, for quick installation
- PIN diode matrix reduces polarity transfer time and digital artifacts, providing consistent picture quality
- 500 mA voltage power pass-through reduces cost by providing satellite receiver path for LNB power
- Built-in amplifier compensates for insertion losses, reducing need of external amplification
- External UL approved power supply reduces heat buildup, thus increasing unit life



Specifications

	Frequency	Insertion Loss	Isolation (input-input)	Isolation (output-output)
TSMS-2150X-16A	950 to 1750 MHz 1250 to 2150 MHz	5 dB 8 dB	25 dB 25 dB	25 dB 25 dB

General

RHCP Switching Voltage	13/14 VDC
LHCP Switching Voltage	17/18 VDC
LNB Current Capacity	500 mA
Dimensions	19" (L) x 2.87" (D) x 1.75" (H)
Weight	5.1 lbs.

Ordering Information

TSMS-2150X-16A Rack-Mounted 2 x 16 Satellite Multiswitch

Specifications Subject To Change Without Notice

Rev 6.0

© Toner Cable Equipment, Inc.