

TFT769900 Series 1310 nm Fiber Optic Transmitters


 Televés


The Televés 769900 optical transmitters represent the latest in design and technology in RF fiber optic transmitters. These transmitters feature a 1310 nm optical output for SMATV or 2 way cable TV system transmissions where RF over fiber works best.

It has a 54-2400 MHz bandwidth so it is compatible with satellite L-band and DOCSIS 3.1 systems. These fiber transmitters are equipped with automatic gain control (AGC), and use cooled DFB lasers for stability. They are built in a 1 RU 19" rackmount chassis with universal 100-253 VAC power supply.

Features:

- 47-2400 MHz Bandwidth
- 6 dBm or 10 dBm Optical Output
- 1310 nm
- DFB Laser
- 0-14 dB Manual Gain Adjustment
- Key Control for Safety
- AGC
- SC/APC Optical Connector
- 12-32 dBmV Input Level Range
- 1RU Rackmount
- Model 769902 (6 dBm)
- Model 769903 (10 dBm)

Ordering Information:

TFT769902	1310 nm, 6 dBm Optical Transmitter
TFT769903	1310 nm, 10 dBm Optical Transmitter

TFT769900 Series 1310 nm Fiber Optic Transmitters

RF Parameters	Bandwidth	47... 2400 MHz
	Input Level Range RF	15...30 dBmV
	Input Level Satellite	RF – 10 dB
	Manual Gain Adjustment	0 ... 14 dB (2 dB steps)
	AGC Range	20 dB
	Flatness (47...1218MHz)	± 0.5 dB
	Flatness (950...2400MHz)	± 2 dB
	Return Loss (47...1218MHz)	≥ 10 dB
	Return Loss (950...2400MHz)	≥ 7 dB
	Impedance	75 Ohm
	CSO (CENELEC 42)	≥ 60 dB
	CTB (CENELEC 42)	≥ 60 dB
	C/N	>50 dB
Optical	Laser	DFB
	Wavelength	1310 nm
	Output Level 769902	5 dBm (3.2 mW)
	Output Level 769903	10 dBm (10 mW)
	Connector	SC/APC (Green)
	Power Supply Voltage	99 to 253 VAC
General	Power Supply Frequency	50 or 60 Hz
	Power Consumption	≤ 25 Watts
	Size W x H x D	19" x 1.75" x 8"
	Weight	7 lbs
	Temperature Range	32° - 110° F