

232105 FO Kit With Professional Fusion Splicer

Professional fusion splicer equipped with six alignment engines to work on the different axes, capable of performing an optical fibre fusion in 9 seconds. Furthermore, fusion is automatically started with the cover closure. It also allows the fusion of pre-configured connectors, thus connectorizing the fibre.

Design optimized to work in any environment, even in the most stringent conditions. Besides, it prevents dust from entering the fusion area, thus ensuring an unsurpassable quality of the overall procedure.

The menu-based user interface is easy and intuitive.

The highly-resistant ABS case containing the kit has a second function besides transportation: thanks to its grooved design it can be used as a working table, making it possible to work virtually anywhere. The following accessories are also included:



- Fibre cleaver with removable pick-up feature (cutting blade specified for 16,000 cuts)
- Precision fibre stripper (pre-set for 250µm and 900µm)
- Isopropyl alcohol tank
- Plastic clamp
- Mount for fibre protection cooling
- Set of spare electrodes (2 items)
- Case and fusion splicer straps
- Regular and lighter-type chargers with USB connector allowing the recharge of other devices (5V,2A)
- User-removable lithium battery

Ref.232105 Languages: English, German, Portuguese and Spanish

Art.Nr	*
EAN13	8424450205464

Ref.232106 Languages: English, French, Italian and Polish

Art.Nr	
EAN13	8424450208908

Main features

- Core-based fibre alignment
- 360° protection: dust, water, and shock proof
- Discharge self-calibration based on altitude and atmospheric pressure
- Calibration option based on the type of the fibre being used
- Automatic oven activation upon tube insertion
- Each of the six high-precision engines is equipped with the stepper motor operation mode, with a permanent magnet and gearbox for maximum precision
- Temperature sensor activated cooling system
- Equipment automatic self-check option
- Configurable ECO mode (auto shut down and stand-by)
- Datalog for fusion data and image export, without any external software installation
- Up to 250 fusions/bakings with a single battery charge
- Two independent connectors (battery and splicer), possibility of working w/o the battery connected
- Extraction battery special button that avoids accidental extractions
- Horizontal 4.3" LCD screen. Solid plastic protector included, compatible with the rubber band protector

232105 FO Kit With Professional Fusion Splicer

Highlights

- Light-weight, reduced-dimensions professional fusion splicer (1,5Kg w/o battery)
- The bumper protector made of high-density rubber provides a high impact resistance
- Endures high wind speeds and other stringent environmental conditions
- Easy and intuitive user interface
- Fusion quality verification by means of a traction procedure followed by the calculation of optical losses
- The cutting angles are measured to detect a poorly set cleaver
- Detects errors in the fibre - usually due to dirt - prior to the fusion taking place

Technical specifications

General		
Average loss per splice	dB	0.02 @ Single Mode fiber (SM) 0.01 @ Multi Mode fiber (MM) 0.04 @ DS fiber and NZDS fiber 0.02 @ BIF fiber and UBIF fiber
Average time per splice	s	9 / 7 (fast mode)
Average time for the heat-shrink sleeve heating	s	19
Fusion programmes		100 90 free and 10 factory pre-defined
Heating programmes		100 96 free and 4 factory pre-defined
Fiber alignment		Core alignment and cladding alignment in three axis X-Y-Z
Screen		High performance 4.3" LCD
Lens magnification		X-Axis + Y-Axis = 180 X-Axis or Y-Axis = 360
Electrodes life	uses	4000 (aprox.) 8000 (with spare)
Records		
Max. result record		10000
Interfaces		
Mini USB		Updates and records download
Powering		
Mains voltage	Vac	100 - 240
Mains frequency	Hz	50 / 60
Battery		Li-ION (11.1V and 7800mAh)
Charging battery duration	cycle	300 aprox. (splicing and heating)
Operating range		
Operating temperature	°C / °F	-20 ... +55 / -4 ... +131
Relative humidity	%	< 95
Altitude	m	0 - 5000