



## < 8!! BN=D' =DHJ '8YVEXYf

- Versatile ZIXI-Embedded STB for Receiving and Playing ZIXI Network Streams
- Intuitive Interface
- Feature-Rich Technology at a Competitive Price



Receive and Play **Live Streams** and View in Full 1080p Resolution



Upload and Play **Music** from a Library or External USB's



Upload and View **Pictures** from a Library or from the Web



Surf the Internet with the Z-Box's **Web Browser**



Upload **Movies** or **Digital Signage Video** and display in High-Def



Enjoy **Error-Free Live HD** Streamed Events over the Internet



Program, Set Up, and Use Robust **On-Board System** Functions

## < 8!! BN=D'DHU '8YV&XYf

( «® ¥¥Š" partners with ZIXI® to bring you the fl~ ) " . Ł\$, a feature-rich HD IPTV Set-top box/media -iŠµj ® embedded with Zixi-Receiver software. It is engineered to maximize both high quality video and audio -iŠµ through from internal or external sources. The Z-Box can be deployed in almost any network worldwide. Designed to decode MPEG-2/H.264 (MPEG-4) codecs, it is a must-have for every Zixi distribution system.

INTERFACES	
<b>Inputs</b>	Ethernet: 10/100/1000BaseT (RJ-45) USB: 2X USB 2.0, 1X USB 3.0 IR 1-Input 3.55mm
<b>Outputs</b>	HDMI 1.4a 10-pin Mini Din (Component / Composite L/R Audio) 4-IR 3.5mm Optical S/PDIF RS-232 (DB-9)
CONTROL	
<b>System Functions</b>	Infrared Setup Customization (with included Hand-held Remote) UART Output Customization, Ser2Net Support Services Supported: Samba/FTP/SFTP Field Upgradable
CODECS	
<b>Video</b>	MPEG-2 MP@HL, H.264 HP@L5.1
<b>Audio</b>	Audio Codec - MPEG-1 Layer II, MPEG-2 AAC, MPEG-4 AAC, Dolby Digital AC-3 PassThrough Only
VIDEO RESOLUTION OUTPUT	
<b>Video</b>	Resolution - 1080p60Hz, 1080p50Hz, 1080i60Hz, 1080i50Hz, 720p60Hz, 720p50Hz
FORMATS SUPPORTED	
<b>Video</b>	ts, m2ts, mkv, avi, mp4
<b>Audio</b>	mp3, m4a, wma, aac
<b>Photo</b>	jpeg, png, bmp, gif
ACCESSORIES	
<b>Hardware</b>	Remote Control (On/Off, Volume Control, Mute, Function Control) Regional Power Supply IR Emitters / Receivers
GENERAL	
<b>Dimensions</b>	236mm x 155mm x 35mm
<b>Weight</b>	940 g / 2.1 lbs.
<b>Power</b>	12V DC
<b>Operating Temp.</b>	0°C to 40°C
<b>GUI</b>	Setup / Control
<b>RoHS Status</b>	Compliant

\* Specifications subject to change without notice