

: 5 A 'GYfjYg' %&&\$ A <n'5H/bi Urcf'DUXg

FAM 1.2 GHz Attenuators



FEATURES

- 5-1220 MHz
- Tin/Nickel Plated Solid Brass
- 100 dB RFI Minimum
- Female to Male Fittings
- 22 Gauge Steel Center Pin
- 9 Different Values

FREQUENCY RANGE: 5-1220 MHz
IMPEDANCE: 75 ohms IN and OUT
ACCURACY: 6% or $\pm .5$ dB

SPECIFICATIONS

MODEL	FAM-18	FAM-28	FAM-38	FAM-6	FAM-8	FAM-10	FAM-12	FAM-16	FAM-20
ATTENUATION (dB)									
5-600 MHz	0.9	2.2	2.7	5.6	7.9	10	12	16	20.1
600-750 MHz	1	2.1	3.4	6.3	8	10.1	12.1	16.1	20.2
750-900 MHz	1.1	2.2	3.4	6.3	8	10.1	12.1	16.2	20.2
900-1000 MHz	1.1	2.3	2.5	5.5	8.1	10.2	12.2	16.2	20.3
1000-1220 MHz	1.1	2.3	2.5	5.7	8.1	10.2	12.2	16.3	20.4
RETURN LOSS (dB) minimum									
5-600 MHz	24	23	23	26	26	22	22	26	22
600-750 MHz	22	21	21	24	22	21	21	22	22
750-900 MHz	22	22	22	22	22	22	22	22	22
900-1000 MHz	22	22	22	22	22	22	22	22	22
1000-1220 MHz	20	20	20	20	20	20	20	20	20