

C1200+ QAM/Analog Signal Level Meter





Features

- QAM/Analog TV Analysis: Level, Tilt, C/N, Scan and Trunk Voltage
- Digital TV Analysis: Power Level, MER and BER
- 128x64 pixels LCD with back-light
- Large lithium battery capacity, over 4 hours working time
- Software upgrade and channel plan edit via USB interface

The C1200+ SLM is specially designed for installation and field technicians seeking to quickly ensure the quality of digital and analog cable services. With streamlined appearance design and simple user interface, C1200+ offers the most cost effective choice for a variety of applications.

Specifications

Analog CATV	
Frequency Range	5 ~ 1010MHz
Level	-30 ~ 60dBmV
Accuracy	±2.0dB
Resolution & Bandwidth	300K
C/N	>50dB
C/N Accuracy	±3.0dB
Others	Channel Scan,Tilt,Trunk Voltage
QAM	
Frequency Range	46 ~ 1010MHz
Power Level	-20dBmV ~ 50dBmV
Power Level Accuracy	±2.0dB
MER	>40
MER Accuracy	±2.0dB
BER	1E-3~1E-9
Modulation Type	16/32/64/128/256QAM(J.83A/C), 64/256QAM(J.83B)
SR	4~7Msp/s
Interface	
RF Input	75Ω F Female Type
AC Adapter	12V/1.2A
USB	Mini-USB
Battery	
Voltage	7.4V/1.6AH
Working Time	>4 hours
Charging Time	3 hours
Other Specifications	
Dimensions (H×W×D)	153mm x 93mm x 42mm (6.0" x 3.7" x 1.7")
Weight	358g



Ordering Information

SKU No.	Description
C1200+	Mini Signal Level Meter, 46 MHz ~ 1010 MHz, 75Ω or BNC

The C1200 comes complete with a padded carrying case, AC charger, USB cable for updates, user manual, and instruction CD.