

Impulse 400D 4K UHD Receiver/Decoder IRD



The Impulse 400D is a powerful and cost-effective 4K UHD receiver decoder/IRD that supports MPEG-2/H.264/H.265/ AVS+/AVS2 UHD/HD/SD video decoding and major audio decoding.

With many tuner input options and multiple input/output interfaces, it can achieve the RF signal reception, program descrambling, multiplexing, downscaling and decoding output that you need.


With IP-based stream processing and management interfaces, it is ideal to support advanced content distribution, 4K decoding, content remultiplexing, digital signal turnaround and transmission via an IP based-headend system.

Key Features

- Receiving
 - Supports ASI and TS-IP input
 - Support for internet delivery protocols (HLS, and SRT)
 - Multiple tuner options to support DVB-S2X, S2, S, T2, T, C (QAM), 8VSB and ISDB-T
 - Supports redundant backup between any two input source
 - Supports Genlock signal input
 - Supports T2-MI transport stream decapsulation (optional)
- Data Processing
 - Two independent common interfaces support multi-channel descrambling, making the unit compliant with various popular CAM modules
 - Embedded BISS-1 & BISS-E supports TS & Service level descrambling
 - PSI/SI/PSIP processing and regeneration
 - Supports TS & Service multiplexing and demultiplexing
 - Supports TS & EIT pass-through
- Output
 - MPEG-2/H.264/H.265/AVS+/AVS2 UHD/HD/SD video decoding
 - HDMI2.0, 3G-SDI output
 - SDI output with 1 embedded audio and expandable to 2 embedded audios (future)
 - Up to 2 pairs of balanced analogue audio and 2 pairs of unbalanced AES/EBU audio output via DB15 connector (1 by default, 2 is a future option)
 - Up to 2 pairs of unbalanced analog audio output via BNC connector(1 by default, 2 is a future option)
 - Multicast and unicast broadcasting in LAN and WAN network via two GbE ports
 - GPI alarm output (reserved for future use)
 - Two TS over IP output ports
 - Two ASI output ports
- Management
 - 1 Ethernet 10/100Base-TX, RJ45
 - Web-based user interface
 - Front panel LCD screen and control buttons

Impulse 400D 4K UHD Receiver/Decoder IRD

SPECIFICATIONS



RF

DVB-S/S2/S2X Input

Input	2 x RF (F-type), 75Ω
Constellation	QPSK, 8PSK, 16APSK, 32APSK, 64APSK
Symbol Rate	1~45 MSps
Input Frequency	950~2150 MHz
Max Bit-rate	150Mbps
Signal Level	-65~-25 dBm
LNB Power	DC 13/18V@350mA
Control Tone	22K on/off
Roll-off Factors	0.35, 0.25, 0.20, 0.15, 0.10, 0.05

DVB-C Input (QAM)

Input	2x RF (F-type), 75Ω
Symbol Rate	1~6.952 MBauds

DVB-C (QAM) Type

Input Frequency Range	48-862 MHz
MaxBit-rate	55Mbps
Signal Level	40-100dBuV (64QAM) 44-100dBuV (256QAM)

8VSB Input

Input	2x RF (F-type), 75Ω
Bandwidth	6MHz
InputFrequency Range	57 -803 MHz (fixed frequency)
Signal Level	-83~-8dBm
Channel Plans	Broadcast
Max Bit-rate	19.39 Mbps

DVB-T Input (QAM)

Input	2x RF (F-type), 75Ω
Constellation	QPSK/16QAM/64QAM
Bandwidth	6/7/8M
Input Frequency Range	48~862 MHz
Max Bit-rate	31.67Mbps
Signal Level	-65~-25dBm
Transmission Mode	2K, 8K
FEC Mode	1/2, 2/3, 3/4, 5/6, 7/8
Guard Interval	1/4, 1/8, 1/16, 1/32

RF

DVB-T2 Input

Input	2x RF (F-type), 75Ω
Constellation	QPSK/16QAM/64QAM/256QAM
Bandwidth	6MHz, 7MHz, 8MHz
Input Frequency Range	48~862 MHz
Max Bit-rate	50.1Mbps
Transmission Mode	1K, 2K, 4K, 8K, 16K, 32K
FEC Mode	1/2, 3/5, 2/3, 3/4, 4/5, 5/6
Guard Interval	1/4, 1/8, 1/16, 1/32, 1/128, 19/256, 19/128

ISDB-T/Tb Input

Input	2x RF (F-type), 75Ω
Constellation	QPSK/16QAM/64QAM
Bandwidth	6MHz
Input Frequency Range	48~862 MHz
Max Bit-rate	23.42Mbps
Signal Level	-65~-10 dBm
Carriers Mode	2K/4K/8K
FEC Mode	1/2, 2/3, 3/4, 5/6, 7/8
Guard Interval	1/4, 1/8, 1/16, 1/32

TS/IP

GbE IP

Interface	2x GbE RJ-45 Ethernet Ports
Package Format	UDP, RTP, SRT, HLS
Traffic Type	Multicast and Unicast
FEC	Pro MPEG CoP3 SMPTE2022 (input & output)(Future)
TCP/IP Protocol	IPv4
IGMP	Version1, 2 & 3
TS Bitrate	UDP/RTP: up to 150 Mbps HLS: up to 20Mbps SRT: up to 30Mbps

Impulse 400D 4K UHD Receiver/Decoder IRD

SPECIFICATIONS

DVB De-scrambling

DVB Common Interface 2 slots	
Bit-rate	Max. 150Mbps (Depend on processing capability of CAM module)
CAM Supported	NEOTON, SMIT, ASTON and other major CAMs
CAS Supported	CONAX, IRDETO, Novel-SuperTV, CTI and other major CAS
BISS-1& BISS-E	Program level, Decoded Service only TS level (future licensed option)
Number of Services	Limited by CAM

Decoder

Interface

Genlock Input	1xBNC, Black Burst/Tri-level sync
SD/HD/3G-SDI Output	2xBNC, 75Ω
Digital Output	1xHDMI 2.0 connector
Analog Audio Outputs	4xBNC, 75Ω unbalanced 2 pairs of analogue balanced audio output via 1x15 Pin D-sub (4xXLR Breakout Cable) (1 by default, 2 is a future option)
AES/EBU	2 pairs of digital unbalanced AES/EBU output via 1x15 Pin D-sub (2xBNC, Breakout Cable) (1 by default, 2 is a future option)

Video Decoding

Video Profile/Levels	MPEG-2 SD 4:2:0 MP@ML- MPEG-2 HD 4:2:0 MP@ML H.264 SD MP@L3 H.264 HD MP@L4.1/HP@L4.1 H.265 Main/Main 10 profile@L5.1 High-tier AVS-P 16(AVS+) AVS2 P2 10-bit Profile @Level 8.2.60
Output Format	720x576i@25 720x480i@29.97,30 720x480p@50,59.94,60 1280x720p@50,59.94,60 1920x1080i@25,29.97,30 1920x1080p@25,30,50,59.94,60 3840x2160@25,30,50,60
Aspect Ratio Conversion	4:3 letterbox, 4:3 pan and scan 16:9 letterbox, 16:9 pan and scan

Audio Decoding

Number of Audio Pairs	2* (future, currently 1 pair)
Audio Codecs Supported	Mpeg-1 Layer II Dolby Digital/AC-3 Dolby Digital Plus/E-AC3 AAC-LC, HE-AAC, HE-AACv2
SDI Embedded Audio Output	2* (future, currently 1 pair)
Adjustable Volume Level	-63~0dB

DVB-ASI

Interface	4 BNC, 75Ω (2xASI input, 2xASI output)
Max Bit-rate	150Mbps
Packet Type	Input:188 and 204 bytes Output: 188 bytes
Input Mode	Spread and burst
Output Mode	Spread

Ancillary Data Support

SDI ANC Data	Closed Captions (CEA/EIA-708)
SDI VBI Waveform	Line 21 Captions (CEA/EIA-608)
DVB Subtitle	DVB subtitle burning (ETSI EN 300 743)

Management

Connector	RJ-45 10/100Mbps - auto negotiation
Protocols	HTTP
User Interfaces	Full control via web GUI Front panel
Firmware Updates	Via web GUI

Physical & Environment

Power Supply	100~240 VAC 50/60Hz
Size	1RU rack mount chassis
Dimension	483mm x 312mm x 44mm
Operating Temperature	0°C ~50°C
Storage Temperature	-10°C ~70°C
Relative Operating Humidity	< 95% (non-condensing)

Order Information

Model	Description
Impulse 400D	Impulse Receiver Decoder SDI/HDMI outputs, IP/ASI in/out, HLS in, H.264/ MPEG-2 video and MPEG1L2, AC3, AAC audio decoding Genlock
Optional Modules	NOTE: Unit can't be ordered with receiver module!!!!
Impulse 40010	DVB-S/S2/S2X Receiver Module
Impulse 40030	QAM-A/C Receiver Module
Impulse 40040	DVB-T/T2 Receiver Module
Impulse 40050	ISDBT Receiver Module
Impulse 40060	8VSB Receiver Module x 1 Input
Impulse 400D XLR Cable	XLR Audio Breakout Cable
Additional Decoder Licenses	
Impulse 40300	Closed Captioning License
Impulse 40310	Input Redundancy License
Impulse 40320	Multiplexing License
Impulse 40330	TS-Level BISS Decryption License
Impulse 40340	T2MI License
Impulse 40410	SRT Input License